

MATERIAL SAFETY DATA SHEET

March 2008

SECTION 1 – PRODUCT AND COMPANY IDENTIFICATION

Product Name: INSTAbond® 392 Anaerobic Pipe Thread Sealant
NSN # 8030-01-054-0740

Company: ACCRABond Inc.
8848 Hacks Cross Road
Olive Branch, MS 38654

Emergency Phone Numbers: ACCRABond Inc. (662) 895-4480
CHEMTREC (800) 424-9300

SECTION 2 – INFORMATION ON COMPONENTS

Chemical Name	CAS Number	Weight %	ACGIH TLV	ACGIH STEL	OSHA PEL-TWA	SKIN
Methacrylated Polyol	25852-47-5	40 - 55	N/E	N/E	N/E	No
Dialkyl Ester	Proprietary	20 - 35	N/E	N/E	N/E	No
Acrylic Copolymer	96-33-3	5 - 10	N/E	N/E	N/E	No
Polytetrafluoroethylene	9002-84-0	1 – 5	N/A	N/A	N/A	No
Cumene Hydroperoxide	80-15-9	0.1 – 1.0	50 ppm	N/E	N/E	Yes
Sodium Sulfimide	81-07-2	0.1 – 1.0	N/E	N/E	N/E	No

SECTION 3 – HAZARDS IDENTIFICATION

INGESTION: May be moderately toxic.

SKIN: May cause moderate skin injury (reddening, swelling) and/or sensitization which may not occur immediately. Prolonged contact with this product may cause burns.

INHALATION: Even though product has low volatility, vapors can be irritating.

EYES: Will cause eye irritation and possible eye injury.

TARGET ORGANS: None known.

HMIS RATING: Health – 2 Flammability – 1 Reactivity – 0

SECTION 4 – FIRST AID MEASURES

INGESTION: Do not induce vomiting. Have victim rinse out mouth with water, then drink sips of water to remove taste from mouth. Get medical attention. If vomiting occurs spontaneously, keep head below hips to prevent aspiration.

SKIN: Remove contaminated clothing and wash contact area with soap and water for 15 minutes. If dermatitis occurs, seek medical attention.

INHALATION: In case of exposure to high concentration of vapors, remove person to fresh air. If respiratory irritation persists, seek medical attention.

EYES: Immediately flush with plenty of water (under eye lids) at least 15 minutes. If redness, burning, blurred vision or swelling persists, consult a physician immediately.

SECTION 5 – FIRE FIGHTING MEASURES

FLASHPOINT: > 200° F (Setaflash)

EXTINGUISHING MEDIA: Use water fog, foam, dry chemical or carbon dioxide to extinguish flames.

SPECIAL FIRE FIGHTING MEASURES: Firefighters should wear full protective clothing and self-contained breathing apparatus. Thoroughly decontaminate fire fighting equipment and fire fighting apparel after the incident.

SECTION 6 – ACCIDENTAL RELEASE MEASURES

ACCIDENTAL RELEASE MEASURES: In the event of a spill, immediately remove any source of ignition. Using appropriate personal protective equipment and non-sparking tools, contain spilled material. Cover the liquid with inert absorbent. Scoop all contaminated material into containers for proper disposal.

SECTION 7 – HANDLING AND STORAGE

HANDLING AND STORAGE: Store below 100° F for maximum stability. Do not store in direct sunlight or near high heat sources. To prevent loss of inhibitor, do not blanket or sparge with nitrogen. Store samples in original packaging. If product has solidified, do not attempt to use. Wash skin thoroughly with soap and water after handling. Solvents should not be used to clean hands or skin because they increase the penetration of the material into the skin.

SECTION 8 – EXPOSURE CONTROLS/PERSONAL PROTECTION

VENTILATION: Good air circulation and ventilation is adequate.

RESPIRATORY PROTECTION: A respirator protection program that meets OSHA 1910.134 must be followed whenever workplace conditions warrant the use of a respirator.

SKIN PROTECTION: Butyl or nitrile gloves should be used along with appropriate clothing.

EYE PROTECTION: Chemical splash safety eyewear is always recommended.

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE:	White to off-white paste
ODOR:	Benign
SPECIFIC GRAVITY:	1.20
SOLUBILITY IN WATER:	Insoluble
VAPOR PRESSURE:	N/A
VOLATILE ORGANIC CONTENT:	< 20 grams/liter

SECTION 10 – STABILITY AND REACTIVITY

STABILITY:	This product is stable under normal conditions.
HAZARDOUS POLYMERIZATION:	Hazardous polymerization may occur. Uncontrolled polymerization may cause rapid evolution of heat and increase in pressure that could result in violent rupture of sealed containers.
HAZARDOUS DECOMPOSITION PRODUCTS:	Hazardous decomposition products may include oxides of carbon and nitrogen, hydrocarbon fragments and organic decomposition fragments.
INCOMPATIBILITY:	Free radical initiators, including peroxides, strong oxidizing agents, copper, copper alloys, carbon steel, iron-containing constituents, and strong bases.
CONDITIONS TO AVOID:	Storage above 100° F, exposure to direct sunlight or other UV sources, loss of dissolved air or polymerization inhibitor, contamination with incompatible materials.

SECTION 11 – TOXICOLOGY INFORMATION

Component	Oral LD50	Dermal LD50	Inhalation LC50
Methacrylated Polyol	Not Determined	Not Determined	Not Determined
Dialkyl Ester	Not Available	Not Available	Not Available
Acrylic Copolymer	Not Determined	Not Determined	Not Determined
Polytetrafluoroethylene	Not Available	Not Available	Not Available
Cumene Hydroperoxide	2000 mg/kg (rat)	1500 mg/kg (rat)	220 ppm (4 hrs)
Sodium Sulfimide	17,000 mg/kg (mouse)	Not Available	Not Available

SECTION 12 – ECOLOGICAL INFORMATION

ECOLOGICAL INFORMATION:	Keep product from entering waterways. No additional ecological data is available on this product.
-------------------------	---

SECTION 13 – DISPOSAL INFORMATION

DISPOSAL INFORMATION: Dispose of in accordance with federal, state and local regulations.

SECTION 14 – TRANSPORTATION INFORMATION

UN OR ID NUMBER: Unrestricted. No Listing.
PROPER SHIPPING NAME: Not Regulated.
ITA: Not Regulated.
HAZARD CLASS/DIVISION: Not Regulated.
GROUND TRANSPORTATION: Not Regulated.
DOT: 49 CFR Part 172

SECTION 15 – REGULATORY INFORMATION

SARA TITLE 313: Cumene Hydroperoxide (80-15-9).
TSCA 12 (B): No substances found that require reporting.
CERCA-SARA HAZARD CATEGORY: As defined, this material is considered a chronic health hazard and a reaction hazard.
CALIF PROPOSITION 65: This product contains saccharin which is known to cause cancer in laboratory animals. If the material is used as intended, there is no requirement for Proposition 65 hazard warning.

SECTION 16 - OTHER

To the best of our knowledge, the information contained herein is accurate. However, no liability whatsoever is assumed for the accuracy or completeness of the information contained herein. Final determination of suitability of any materials is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.